

Part Number: 9595282802

95 EER CORE SET

**EER cores, similar to ETD cores, have been designed to make optimum use of a given volume of ferrite material for maximum throughput power. The structure, which includes a round center post, approaches a nearly uniform cross-sectional area throughout the core and provides a winding area that minimizes winding losses.**

EER cores can be supplied with the center post gapped to a mechanical dimension or an  $A_L$  value.

[Catalog Drawing](#)  
[3D Model](#)


Weight indicated is per pair or set.

Weight: 28 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	28.5	± 0.60	1.122	—
B	14	± 0.20	0.551	—
C	11.4	± 0.30	0.449	—
D	9.6	± 0.20	0.378	—
E	21.2	min	0.835	min
F	9.9	± 0.30	0.39	—

### Chart Legend

$\Sigma l/A$  : Core Constant,  $l_e$  : Effective Path Length,  $A_e$  : Effective Cross-Sectional Area,  $V_e$  : Effective Core Volume

$A_L$  : Inductance Factor 

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties	
$A_L$ (nH)	3500 ±25%
$A_e$ (cm <sup>2</sup> )	0.859
$\Sigma l/A$ (cm <sup>-1</sup> )	7.3
$l_e$ (cm)	6.29

Electrical Properties	
$V_e(\text{cm}^3)$	5.398
$A_{\text{min}}(\text{cm}^2)$	0.77

$A_L$  value is measured at 1 kHz,  $B < 10$  gauss.

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288  
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com