

Part Number: 9598261802

98 EER CORE SET

**EER cores, similar to ETD cores, have been designed to make optimum use of a given volume of ferrite material for maximum throughput power. The structure, which includes a round center post, approaches a nearly uniform cross-sectional area throughout the core and provides a winding area that minimizes winding losses.**

EER cores can be supplied with the center post gapped to a mechanical dimension or an  $A_L$  value.

[Catalog Drawing](#)  
[3D Model](#)


Weight indicated is per pair or set.

Weight: 11.2 (g)

| Dim | mm   | mm tol | nominal inch | inch misc. |
|-----|------|--------|--------------|------------|
| A   | 25.5 | ± 0.50 | 1.004        | —          |
| B   | 9.3  | ± 0.15 | 0.366        | —          |
| C   | 7.5  | ± 0.25 | 0.295        | —          |
| D   | 6.4  | ± 0.15 | 0.252        | —          |
| E   | 19.8 | min    | 0.78         | min        |
| F   | 7.5  | ± 0.25 | 0.295        | —          |

### Chart Legend

$\Sigma l/A$  : Core Constant,  $l_e$  : Effective Path Length,  $A_e$  : Effective Cross-Sectional Area,  $V_e$  : Effective Core Volume

$A_L$  : Inductance Factor 

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

| Electrical Properties            |           |
|----------------------------------|-----------|
| $A_L$ (nH)                       | 1800 ±25% |
| $A_e$ (cm <sup>2</sup> )         | 0.434     |
| $\Sigma l/A$ (cm <sup>-1</sup> ) | 11.1      |
| $l_e$ (cm)                       | 4.8       |

| Electrical Properties         |       |
|-------------------------------|-------|
| $V_e(\text{cm}^3)$            | 2.083 |
| $A_{\text{min}}(\text{cm}^2)$ | 0.425 |

$A_L$  value is measured at 1 kHz,  $B < 10$  gauss.

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288  
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com