

Part Number: 9578394002

78 ETD CORE SET

ETD cores have been designed to make optimum use of a given volume of ferrite material for maximum throughput power, specifically for forward converter transformers. The structure, which includes a round center post, approaches a nearly uniform cross-sectional area throughout the core and provides a winding area that minimizes winding losses. ETD cores are used mainly in switched-mode power supplies and permit off-line designs where IEC and VDE isolation requirements must be met.

□ETD cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

[Catalog Drawing](#)

[3D Model](#)

Weight indicated is per pair or set.

Weight: 60 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	39.1	± 0.70	1.539	—
B	19.8	± 0.20	0.78	—
C	12.7	± 0.35	0.5	—
D	14.6	± 0.20	0.575	—
E	29.3	min	1.154	min
F	12.7	± 0.35	0.5	—

Chart Legend

$\Sigma l/A$: Core Constant, l_e : Effective Path Length, A_e : Effective Cross-Sectional Area, V_e : Effective Core Volume

A_L : Inductance Factor

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties	
A_L (nH)	3000 ±25%
A_e (cm ²)	1.28

Electrical Properties	
$\Sigma l/A(\text{cm}^{-1})$	7.2
$l_e(\text{cm})$	9.24
$V_e(\text{cm}^3)$	11.85
$A_{\text{min}}(\text{cm}^2)$	1.267

A_L value is measured at 1 kHz, $B < 10$ gauss

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com