

Part Number: 9498112002

98 E CORE SET

The E core geometry offers an economical design approach for inductive applications in a variety of power designs.

E cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

[Catalog Drawing](#)

[3D Model](#)

Weight indicated is per pair or set.

Weight: 29.9 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	34.5	±1.00	1.358	—
B	14.35	±0.35	0.565	—
C	9.5	±0.40	0.374	—
D	9.7	±0.30	0.382	—
E	25.4	min	1	min
F	9.4	±0.30	0.37	—

Chart Legend

$\Sigma l/A$: Core Constant, l_e : Effective Path Length, A_e : Effective Cross-Sectional Area, V_e : Effective Core Volume

A_L : Inductance Factor

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties	
A_L (nH)	2900 ±25%
A_e (cm ²)	0.86
$\Sigma l/A$ (cm ⁻¹)	8.1
l_e (cm)	6.97
V_e (cm ³)	5.99
A_{min} (cm ²)	0.79

A_L value is measured at 1 kHz, $B < 10$ gauss.

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com