Fair-Rite Products Corp.
Your Signal Solution®

Flat Cable Snap-Its (0443164051)

Part Number: 0443164051

43 FLAT CABLE CORE ASSEMBLY

Explanation of Part Numbers:
– Digits 1 & 2 = Product Class
– Digits 3 & 4 = Material Grade

Flat Cable Snap-Its for use on multi-conductor flat cables to suppress common-mode conducted EMI from 1MHz to hundreds of MHz. These Flat Cable Snap-Its are available in two ferrite materials, 31 and 43. The polypropylene cases are meeting the RoHS restrictions of hazardous substances and have a flammability rating of UL 94 V-0.

The Expanded Cable and Suppressor Kit (Part number 0199000005) contains several Flat Cable Snap-It assemblies.

Catalog Drawing
3D Model

Weight: 130 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	80.8	_	3.18	_
B	65.3	_	2.57	_
C	32.3	_	1.272	_
D	8.1	_	0.32	_

Cable Information			
Max Diameter	Max Dimension	Solid Equivalent	Flat Cable Cores
0 0	64.00 x 1.30	_	-

Chart Legend
+ Test frequency


Typical Impedance (Ω)	
10 MHz	54
25 MHz+	94
100 MHz+	217
250 MHz	353

Flat Cable Snap-It assemblies are controlled for impedances only. Minimum impedance values are specified for the + marked frequencies. The minimum impedance is typically the listed impedance less 20%.

Catalog Drawing

Centered, single turn impedance tests on the 31 and 43 material parts are performed on the E4991A/HP4291B Impedance Analyzer. Cores are tested with the shortest practical wire length.

Typical Impendance (Ω)	
10 MHz	48
25 MHz^{+}	100
100 MHz^{+}	290
250 MHz	420



CSV Download

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com